

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 32335
Trade name/designation

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Printing aid

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

A. M. Ramp & Co. GmbH

RUCO Druckfarben

Lorsbacher Str. 28

D-65817 Eppstein

Telephone: +49.61 98.30 40

Telefax: +49.61 98.3 22 88

Department responsible for information:

E-mail info@ruco-inks.com

1.4. Emergency telephone number

Emergency telephone number +49.61 98.30 40

Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

Skin Irrit. 2 / H315

skin corrosion/irritation

Causes skin irritation.

Eye Dam. 1 / H318

Serious eye damage/eye irritation

Causes serious eye damage.

STOT SE 3 / H335

Specific target organ toxicity (single exposure)

May cause respiratory irritation.

STOT SE 3 / H336

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

STOT RE 2 / H373

Specific target organ toxicity (repeated exposure)

May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 / H304

Aspiration hazard

May be fatal if swallowed and enters airways.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

H318

Causes serious eye damage.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

H373

May cause damage to organs through prolonged or repeated exposure.

H304

May be fatal if swallowed and enters airways.

Precautionary Statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260

Do not breathe vapour.

P280

Wear protective gloves and eye/face protection.

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 32335
 Print date 08.09.2020
 Version 8.0

Revision date 17.04.2020

EN
 Page 2 / 11

P310 Immediately call a POISON CENTER or doctor/ physician.
 P331 Do NOT induce vomiting.
 P370 + P378 In case of fire, use sand, extinguishing powder or alcohol resistant foam.
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazard components for labelling

Cyclohexanone
 Xylene
 Ethyl acetate

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description Organic solvent or solvent mixture

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Designation classification: // Remark	weight-%
205-500-4 141-78-6 607-022-00-5	01-2119475103-46-XXXX Ethyl acetate Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	25 - 50
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32-XXXX Xylene Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / STOT RE 2 H373 / STOT SE 3 H335	25 - 50
203-631-1 108-94-1 606-010-00-7	01-2119453616-35-XXXX Cyclohexanone Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Dam. 1 H318	10 - 20
202-849-4 100-41-4 601-023-00-4	01-2119489370-35-XXXX ethylbenzene Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 2 H225	5 - 10
204-658-1 123-86-4 607-025-00-1	01-2119485493-29-XXXX n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	5 - 10
203-625-9 108-88-3 601-021-00-3	01-2119471310-51-XXXX Toluene Flam. Liq. 2 H225 / Repr. 2 H361 / Asp. Tox. 1 H304 / STOT RE 2 H373 / Skin Irrit. 2 H315 / STOT SE 3 H336	0,1 - 0,25

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do

Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 3 / 11

not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store

Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 4 / 11

carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Ethyl acetate

INDEX No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

TWA: 1460 mg/m³; 400 ppm

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

Cyclohexanone

INDEX No. 606-010-00-7 / EC No. 203-631-1 / CAS No. 108-94-1

WEL, TWA: 41 mg/m³; 10 ppm

WEL, STEL: 82 mg/m³; 20 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 2 mmol/mol creatinine

Remark: cyclohexanol; urine; end of exposure or end of shift

ethylbenzene

INDEX No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

TWA: 441 mg/m³; 100 ppm

STEL: 552 mg/m³; 125 ppm

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

TWA: 724 mg/m³; 150 ppm

STEL: 966 mg/m³; 200 ppm

Toluene

INDEX No. 601-021-00-3 / EC No. 203-625-9 / CAS No. 108-88-3

TWA: 191 mg/m³; 50 ppm

STEL: 574 mg/m³; 150 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 180 mg/kg

DNEL acute inhalative (local), Workers: 289 mg/m³

DNEL acute inhalative (systemic), Workers: 442 mg/m³

DNEL long-term inhalative (local), Workers: 221 mg/m³

DNEL long-term inhalative (systemic), Workers: 211 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 5 / 11

Ethyl acetate

INDEX No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

- DNEL long-term dermal (systemic), Workers: 63 mg/kg
- DNEL acute inhalative (systemic), Workers: 1468 mg/m³
- DNEL long-term inhalative (systemic), Workers: 734 mg/m³

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

- DNEL acute dermal, short-term (systemic), Workers: 11 mg/kg
- DNEL long-term dermal (systemic), Workers: 11 mg/kg
- DNEL acute inhalative (local), Workers: 600 mg/m³
- DNEL acute inhalative (systemic), Workers: 600 mg/m³
- DNEL long-term inhalative (local), Workers: 300 mg/m³
- DNEL long-term inhalative (systemic), Workers: 300 mg/m³

Cyclohexanone

INDEX No. 606-010-00-7 / EC No. 203-631-1 / CAS No. 108-94-1

- DNEL acute dermal, short-term (systemic), Workers: 100 mg/kg
- DNEL long-term dermal (systemic), Workers: 10 mg/kg
- DNEL acute inhalative (local), Workers: 100 mg/m³
- DNEL acute inhalative (systemic), Workers: 100 mg/m³
- DNEL long-term inhalative (local), Workers: 80 mg/m³
- DNEL long-term inhalative (systemic), Workers: 100 mg/m³

Toluene

INDEX No. 601-021-00-3 / EC No. 203-625-9 / CAS No. 108-88-3

- DNEL long-term dermal (systemic), Workers: 384 mg/kg
- DNEL acute inhalative (local), Workers: 384 mg/m³
- DNEL acute inhalative (systemic), Workers: 384 mg/m³
- DNEL long-term inhalative (local), Workers: 192 mg/m³
- DNEL long-term inhalative (systemic), Workers: 192 mg/m³

PNEC:

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

- PNEC aquatic, freshwater: 0,327 mg/L
- PNEC aquatic, marine water: 0,327 mg/L
- PNEC sediment, freshwater: 12,64 mg/kg
- PNEC sediment, marine water: 12,64 mg/kg
- PNEC, soil: 2,31 mg/kg
- PNEC sewage treatment plant (STP): 6,58 mg/L

Ethyl acetate

INDEX No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

- PNEC aquatic, freshwater: 0,24 mg/L
- PNEC aquatic, marine water: 0,024 mg/L
- PNEC aquatic, intermittent release: 1,65 mg/L
- PNEC sediment, freshwater: 1,15 mg/kg
- PNEC sediment, marine water: 0,115 mg/kg
- PNEC, soil: 0,148 mg/kg
- PNEC sewage treatment plant (STP): 650 mg/L

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

- PNEC aquatic, freshwater: 0,18 mg/L
- PNEC aquatic, marine water: 0,018 mg/L
- PNEC aquatic, intermittent release: 0,36 mg/L
- PNEC sediment, freshwater: 0,981 mg/kg
- PNEC sediment, marine water: 0,0981 mg/kg
- PNEC, soil: 0,0903 mg/kg
- PNEC sewage treatment plant (STP): 35,6 mg/L

Cyclohexanone

INDEX No. 606-010-00-7 / EC No. 203-631-1 / CAS No. 108-94-1

- PNEC aquatic, freshwater: 0,0329 mg/L
- PNEC aquatic, marine water: 0,0033 mg/L

Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 6 / 11

PNEC aquatic, intermittent release: 0,329 mg/L
PNEC sediment, freshwater: 0,0951 mg/kg
PNEC, soil: 0,0143 mg/kg
PNEC sewage treatment plant (STP): 10 mg/L

Toluene

INDEX No. 601-021-00-3 / EC No. 203-625-9 / CAS No. 108-88-3

PNEC aquatic, freshwater: 0,68 mg/L
PNEC aquatic, marine water: 0,68 mg/L
PNEC aquatic, intermittent release: 0,68 mg/L
PNEC sediment, freshwater: 16,39 mg/kg
PNEC sediment, marine water: 16,39 mg/kg
PNEC, soil: 2,89 mg/kg
PNEC sewage treatment plant (STP): 13,61 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

*

Appearance:

Physical state: Liquid
Colour: refer to label

Odour: characteristic

Odour threshold: not determined

pH at 20 °C: not applicable

Melting point/freezing point: not determined

Initial boiling point and boiling range: 77 °C

Flash point: -4 °C

Method: DIN 53213-1 (08/2002: replaced by EN ISO 1523)

Evaporation rate: not determined

flammability

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 1 Vol-%

Upper explosion limit: 11,5 Vol-%

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 7 / 11

Vapour pressure at 20 °C:	100 mbar
Vapour density:	not determined
Relative density:	
Density at 20 °C:	0,89 g/cm³
Solubility(ies):	
Water solubility (g/L) at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Ignition temperature in °C	415 °C
Decomposition temperature:	not applicable
Viscosity at 20 °C:	11 s 4 mm Method: DIN 53211
Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	
Solid content (%):	0 weight-%
solvent content:	
Organic solvents:	100 weight-%
Water:	0 weight-%
Solvent separation test (%):	< 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

ethylbenzene

oral, LD50, Rat: 3500 mg/kg

dermal, LD50, Rabbit: 15400 mg/kg

Ethyl acetate

oral, LD50, Rat: 4934 mg/kg

dermal, LD50, Rabbit: 20000 mg/kg

inhalative (vapours), LC50, Rat: 29,3 mg/L (4 h)

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg

dermal, LD50, Rabbit: 14112 mg/kg

inhalative (vapours), LC50, Rat: 23,4 mg/L (4 h)

Cyclohexanone

oral, LD50, Rat: 1620 mg/kg

*

Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 8 / 11

dermal, LD50, Rabbit: 1100 mg/kg
inhalative (vapours), LC50, Rat: 11 mg/L (4 h)

Toluene

oral, LD50, Rat: 5580 mg/kg
dermal, LD50, Rabbit: > 5000 mg/kg
inhalative (vapours), LC50, Rat: 28,1 mg/L (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye damage.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Xylene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2,6 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 1 mg/L (48 h)

Algae toxicity, ErC50, Selenastrum capricornutum: 2,2 mg/L (73 h)

Bacterial toxicity: NOEC, Activated sludge: 16 mg/L (28 d)

Method: OECD 301 F

ethylbenzene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 4,2 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 1,8 - 2,4 mg/L (48 h)

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 5,4 mg/L (72 h)

Ethyl acetate

Fish toxicity, LC50: 230 mg/L (96 h)

Daphnia toxicity, EC50: 610 mg/L (48 h)

Algae toxicity, ErC50: 5600 mg/L

n-butyl acetate

Fish toxicity, LC50: 18 mg/L (96 h)

Daphnia toxicity, EC50: 44 mg/L (48 h)

Algae toxicity, ErC50: 647,7 mg/L (72 h)

Cyclohexanone

Daphnia toxicity, EC50, Daphnia magna: 820 mg/L (48 h)

*

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 9 / 11

Algae toxicity, ErC50: 32,9 mg/L (72 h)

Toluene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 5,5 mg/L (96 h)

Daphnia toxicity, EC50, Ceriodaphnia spec: 3,78 mg/L (48 h)

Algae toxicity, ErC50, Chlamydomonas angulosa: 134 mg/L (3 h)

Bacterial toxicity, EC50, Nitrosomonas sp: 84 mg/L (24 h)

Long-term Ecotoxicity

n-butyl acetate

Algae toxicity, NOEC: 200 mg/L (72 d)

Toluene

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): 1,39 mg/L (40 d)

Daphnia toxicity, NOEC, Ceriodaphnia spec: 0,74 mg/L (7 d)

12.2. Persistence and degradability

*

Xylene

aerobic, OECD 301 F: 90 % (28 d)

Toluene

: 86 % (20 d); evaluation Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

*

Xylene

Partition coefficient: n-octanol/water: 3,12 - 3,2

Cyclohexanone

Partition coefficient: n-octanol/water: 0,86

Toluene

Partition coefficient: n-octanol/water: 2,73

Bioconcentration factor (BCF)

Xylene

Bioconcentration factor (BCF): 25,9

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

140603* other solvents and solvent mixtures

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID):

Paint related material
(Ethylacetat)

Sea transport (IMDG):

PAINT RELATED MATERIAL

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 32335
 Print date 08.09.2020
 Version 8.0

Revision date 17.04.2020

EN
 Page 10 / 11

	(Ethylacetat)	
Air transport (ICAO-TI / IATA-DGR):	Paint related material	
	(Ethylacetat)	
14.3. Transport hazard class(es)		3
14.4. Packing group		II
14.5. Environmental hazards		
Land transport (ADR/RID)		not applicable
Marine pollutant		not applicable
14.6. Special precautions for user		
Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.		
Advices on safe handling: see parts 6 - 8		
Further information		
Land transport (ADR/RID)		
tunnel restriction code		D/E
Sea transport (IMDG)		
EmS-No.		F-E, S-E
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code		
not applicable		

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture** *
- EU legislation**
- Directive 2010/75/EU on industrial emissions**
 VOC-value (in g/L): 890,500
- National regulations**
- Restrictions of occupation**
 Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
- Other regulations, restrictions and prohibition regulations**
 HMIS-Code: 1-2-0-C
- 15.2. Chemical Safety Assessment**
 Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 32335
Print date 08.09.2020
Version 8.0

Revision date 17.04.2020

EN
Page 11 / 11

Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
Skin Irrit. 2	skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	Specific target organ toxicity (single exposure)	Calculation method.
STOT SE 3	Specific target organ toxicity (single exposure)	Calculation method.
STOT RE 2	Specific target organ toxicity (repeated exposure)	Calculation method.
Asp. Tox. 1	Aspiration hazard	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version